



505201



## Push-button, NC contact + NO contact for hotel card Light control

Technical features

#### Architecture

| Type of control unit | Hotel card               |
|----------------------|--------------------------|
| Technical version    | isolated input terminals |

## Configuration

- 1 NO, 1 NC, separate input terminals

#### Main electrical features

| Nominal voltage | 250 V    |
|-----------------|----------|
| Rated voltage   | 250 V AC |

## **Electric current**

2 A Momentary-contact current

#### Materials

| Material | Plastic/metal |
|----------|---------------|
|----------|---------------|

#### **Dimensions**

| Depth           | 41 mm   |
|-----------------|---------|
| Insertion depth | 31,2 mm |
| Height          | 71 mm   |
| Width           | 71 mm   |

## Installation, mounting

Installation mode with spreader claws

## Connection

| Connection terminals     | according to IEC 60669-1 |
|--------------------------|--------------------------|
| Connection terminals     | according to VDE 0632-1  |
| - with plug-in terminals |                          |

# Equipment

| Quantity of NC contacts  | 1 |
|--|---|
| Quantity of NO contacts  | 1 |
| and he illuminated uning group and aloughous properties. N. Americal |   |

- can be illuminated using neon and glow lamp unit with N-terminalfor lighting and monitoring circuit

# Safety

# Identification

| Application, usage | Light control |
|--------------------|---------------|
| Main design line   | Light control |