



20341606



Thermostat, NO contact, with centre plate, for underfloor heating with rocker switch, external temperature sensor, Berker S.1/B.3/B.7, anthracite, matt

Technical features

Functions

- with on/off switch and 2 LEDs

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 230 V |
| Rated voltage | 230 V AC |
| Frequency | 50/60 Hz |

Electric current

| | |
|-------------------|------|
| Switching current | 10 A |
|-------------------|------|

Materials

| | |
|-----------------------|---------------|
| Colour of design line | anthracite |
| Colour | anthracite |
| Material | Plastic/metal |

LED control

| | |
|-----|---|
| LED | with LED for heating and LED for night lowering |
|-----|---|

Installation, mounting

| | |
|-------------------|------------------------|
| Installation mode | without spreader claws |
|-------------------|------------------------|

Connection

| | |
|---------------------|---|
| Sensor cable length | 4 m |
| Connection | with separate connection for night lowering |
| - | with plug-in terminals |

Settings

| | |
|---------------------------------|------------|
| Floor temperature setting range | 10...50 °C |
| Room temperature setting range | 5...30 °C |

Equipment

| | |
|----------------------------------|--|
| Night lowering | ≈ 5 K |
| Switching temperature difference | ≈ 1 K |
| - | setting knob with temperature range limitation |
| - | e.g. for valve drives closed in de-energised state |

Use

| | |
|--|-----------------------------|
| Differentiation characteristic 1 - Sales | with rocker switch |
| Differentiation characteristic 3 - Sales | external temperature sensor |

Use conditions

| | |
|-------------------------|---------------------|
| Energy efficiency class | I (1%) |
| - | with thermal return |

Identification

| | |
|--------------------------|------------------------------------|
| Application, usage | HVAC control |
| Main design line | Berker S.1/B.3/B.7 |
| Secondary design line(s) | Berker S.1, Berker B.3, Berker B.7 |
