



16408999



## Relay switch with centre plate for hotel card Berker S.1/B.3/B.7, polar white glossy

### Technical features

#### Architecture

Fixing mode	flush-mounting
-------------	----------------

#### Configuration

- 1pole
---------

#### Main electrical features

Nominal voltage	230 V
Rated voltage	230 V AC
Frequency	50/60 Hz

#### Electric current

Inductive load at $\cos \varphi = 0.6$	max. 6 A
Switching current	10 A /230 V AC1

#### Power

Conventional transformers	1500 VA
Electronic transformers	1500 W
Power consumption	< 0.2 W

#### Materials

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	Plastic/metal
Surface appearance	glossy

#### Dimensions

Depth	57,3 mm
Insertion depth	32 mm
Card width	max. 55 mm
Card thickness	0,8...1,2 mm
Height	71 mm
Width	71 mm

#### Fluorescent bulbs control

Compact fluorescent lamps	500 W
Fluorescent lamps in duo circuit	1500 W

#### LED control

LED	illuminated with blue LED if hotel card is not inserted
-----	---------------------------------------------------------

---

**Incandescent bulbs control**

---

230 V incandescent lamps and halogen lamps 1500 W

---

**Installation, mounting**

---

Installation mode with spreader claws

---

**Connection**

---

Screw terminals (max.) 2 x 2,5 mm<sup>2</sup>

---

- with screw-in lift terminals

---

**Settings**

---

Delay time incrementally adjustable 0, 15, 30, 60 s

---

- with potentiometer for incremental adjustment of delay time

---

**Equipment**

---

- for illumination  
- with potential-free contact

---

**Safety**

---

Protection index IP IP20

---

**Use conditions**

---

Operating temperature -5...50 °C

---

Storage/transport temperature -25...70 °C (storage at > 45°C reduces the service life)

---

**Identification**

---

Application, usage Light control

---

Main design line Berker S.1/B.3/B.7

---

Secondary design line(s) Berker S.1, Berker B.3, Berker B.7

---