



29511606



## LED signal light, RGB anthracite matt

### Technical features

#### Architecture

|             |                |
|-------------|----------------|
| Fixing mode | flush-mounting |
|-------------|----------------|

#### Main electrical features

|               |          |
|---------------|----------|
| Rated voltage | 230 V AC |
| Frequency     | 50/60 Hz |

#### Power

|                   |  |
|-------------------|--|
| Power consumption | at 195 ... 265 V~, 50/60 Hz - max. 2 W |
|-------------------|--|

#### Materials

|                       |                          |
|-----------------------|--------------------------|
| Colour of design line | anthracite               |
| Colour                | charcoal                 |
| Colour                | anthracite charcoal grey |
| RAL colour            | RAL 7021 - Black grey    |
| Material              | Plastic/metal            |
| Surface appearance    | matt                     |

#### LED control

|                    |   |
|--------------------|---|
| Quantity LED lamps | 4 |
|--------------------|---|

#### Installation, mounting

|   |                          |
|---|--------------------------|
| For installation in standard wall boxes | according to DIN 49073-1 |
|---|--------------------------|

#### Connection

|                         |         |
|-------------------------|---------|
| Conductor cross-section | 2,5 mm² |
|-------------------------|---------|

#### Settings

- Brightness modifiable via potentiometer

#### Equipment

- Colour sequence can be stopped at any position via the push-button.
- Light colours cold white, warm white, blue, orange, red, green, purple (magenta) and colour sequence callable via push-button
- colour is switchable via an external switch

#### temperatur

|                     |            |
|---------------------|------------|
| Ambient temperature | -5...40 °C |
|---------------------|------------|

#### Identification

|                          |                        |
|--------------------------|------------------------|
| Secondary design line(s) | Berker B.7, Berker B.3 |
|--------------------------|------------------------|

#### Instructions

- For consistent illumination of all pilot lamps, connect max. 5 devices per 10 m of cable length.