



29518982



## LED signal light, RGB

### Technical features

#### Architecture

Fixing mode	flush-mounting
-------------	----------------

#### Main electrical features

Rated voltage	230 V AC
Frequency	50/60 Hz

#### Power

Power consumption	at 195 ... 265 V~, 50/60 Hz - max. 2 W
-------------------	--

#### Materials

Colour of design line	white
Colour	white
Colour	white
RAL colour	RAL 1013 - Oyster white
Material	Plastic/metal
Surface appearance	glossy

#### LED control

Quantity LED lamps	4
--------------------	---

#### Installation, mounting

For installation in standard wall boxes	according to DIN 49073-1
---	--------------------------

#### Connection

Conductor cross-section	2,5 mm <sup>2</sup>
-------------------------	---------------------

#### Settings

- Brightness modifiable via potentiometer

#### Equipment

- Colour sequence can be stopped at any position via the push-button.
- Light colours cold white, warm white, blue, orange, red, green, purple (magenta) and colour sequence callable via push-button
- colour is switchable via an external switch

#### temperatur

Ambient temperature	-5...40 °C
---------------------	------------

#### Identification

Secondary design line(s)	Berker S.1, Berker B.3, Berker B.7
--------------------------	------------------------------------

#### Instructions

- For consistent illumination of all pilot lamps, connect max. 5 devices per 10 m of cable length.