



4588



## Modular UAE socket outlet 8/8pole shielded, cat.6 iso Communication technology

### Technical features

#### Architecture

Design to according to DIN EN 60603-7-51

#### Configuration

- cat.6<sub>A</sub> iso, Class E<sub>A</sub>, shielded

#### Connectivity

- with straight outlet  
- only suitable for RJ45 plugs

#### Main electrical features

Rated voltage 72 V DC

Rated current 0,5 A

#### Voltage

- suitable for PoE+

#### Frequency

Transmission bandwidth max. 500 MHz

#### Resistance

Shield contact resistance 100 mΩ

Signal contact resistance < 20 mΩ

#### Materials

Colour code A and B according to TIA/EIA-568-B.2

Material Plastic/metal

- Housing made of die-cast zinc

#### Dimensions

Insertion depth 35 mm

#### Installation, mounting

Installation mode without spreader claws, for screw fastening

#### Connection

Cat.6A iso/class EA according to DIN EN 50173-1:2011-09

- with IDC terminals  
- with screen contacting 360° and strain relief

#### Equipment

- external eyelets on the supporting ring can be broken off for round designs

---

**Safety**

---

Cat.6 <sub>iso</sub> , Class E <sub>A</sub> , shielded	according to ISO/IEC 11801 A2
Protective screen	according to DIN EN 55022, Class B
Protection index IP	IP20

---

- with optional dust protection hinged covers

---

**Use conditions**

---

Operating temperature	-40...70 °C
-----------------------	-------------

---

**Weight**

---

Weight	≈ 74 g
--------	--------

---

**Identification**

---

Application, usage	Communication technology
Main design line	Communication technology

---