## **product sheet** 3315401909



3315401909 ⊣\_<sub>VGA</sub>

## VGA socket outlet Berker S.1/B.3/B.7, polar white matt

## Technical features

Connectivity
--------------

Connectivity	
<ul> <li>with straight outlet</li> <li>S-VGA compatible</li> </ul>	
<ul> <li>S-VGA compatible</li> <li>with 15pole D-subminiature jack (front)</li> </ul>	
Frequency	
Frequency range video	max. 160 Mł
Screen	
Resolution	max. 1280 x 1024
Materials	
Colour of design line	polar wh
Colour	polarwh
RAL colour	RAL 9010 - Pure wh
Material	Plastic/me
Surface appearance	m
Dimensions	
Insertion depth	12 m
Installation, mounting	
Installation, mounting Installation mode	without spreader claws, for screw fasteni
	without spreader claws, for screw fasteni
Installation mode	
Installation mode Connection	with 15pole D-subminiature double ja
Installation mode Connection Connection	with 15pole D-subminiature double ja
Installation mode Connection Connection with backside jack for connecting to pre-assem Equipment	with 15pole D-subminiature double ja
Installation mode Connection Connection with backside jack for connecting to pre-assem	with 15pole D-subminiature double ja
Installation mode Connection Connection with backside jack for connecting to pre-assem Equipment	with 15pole D-subminiature double ja
Installation mode Connection Connection - with backside jack for connecting to pre-assem Equipment - with supporting ring	with 15pole D-subminiature double ja bled VGA cable
Installation mode Connection Connection with backside jack for connecting to pre-assem Equipment with supporting ring Identification	with 15pole D-subminiature double ja bled VGA cable Communication technolo
Installation mode Connection Connection with backside jack for connecting to pre-assem Equipment with supporting ring Identification Application, usage	with 15pole D-subminiature double ja bled VGA cable Communication technolo Berker S.1/B.3/E
Installation mode Connection Connection with backside jack for connecting to pre-assem Equipment with supporting ring Identification Application, usage Main design line	without spreader claws, for screw fasteni with 15pole D-subminiature double ja bled VGA cable Communication technolo Berker S.1/B.3/E Berker S.1, Berker B.3, Berker E