



3315401404



VGA socket outlet Berker S.1/B.3/B.7, aluminium, matt, lacquered

Technical features

Connectivity

- with straight outlet
- S-VGA compatible
- with 15pole D-subminiature jack (front)

Frequency

Frequency range video max. 160 MHz

Screen

Resolution max. 1280 x 1024 px

Materials

Colour of design line	aluminium
Colour	aluminium
RAL colour	RAL 9006 - White aluminium
Material / workmanship	lacquered
Material	Plastic/metal
Surface appearance	matt

Dimensions

Insertion depth 12 mm

Installation, mounting

Installation mode without spreader claws, for screw fastening

Connection

Connection with 15pole D-subminiature double jack
 - with backside jack for connecting to pre-assembled VGA cable

Equipment

- with supporting ring

Identification

Application, usage	Communication technology
Main design line	Berker S.1/B.3/B.7
Secondary design line(s)	Berker S.1, Berker B.3, Berker B.7

Instructions

Information text For connecting PCs, notebooks, etc. to display devices such as monitors (including LCD monitors) and projectors., Observe the instructions of the cable and device manufacturers for maximum VGA cable lengths!, Fränkische: "Multimedia tube" for laying pre-assembled connection cable, Art. no. 294.10.092, Installation recommendation: Kaiser: "Electronic box" for compliance with the permissible bending radii, Art. No. 1068-02 or 9062-74