product sheet 3315411909



3315411909

Architecture	
Technical version	with screw-in lift terminals
Connectivity	
 with straight outlet S-VGA compatible with 15pole D-subminiature jack (front) 	
Frequency	
Frequency range video	max. 160 MH:
Screen	
Resolution	max. 1280 x 1024 p.
Materials	
Colour of design line	polar whit
Colour	polarwhit
RAL colour	RAL 9010 - Pure whit
Material	Plastic/meta
Surface appearance	mat
Installation, mounting	
motanation, mounting	
	without spreader claws, for screw fastening
Installation mode Connection	without spreader claws, for screw fastening
Installation mode	
Installation mode Connection Conductor cross-section	max. 1,5 mm
Installation mode Connection Conductor cross-section - with screw-in lift terminals for connection to 15-c	max. 1,5 mm
Installation mode Connection Conductor cross-section - with screw-in lift terminals for connection to 15-c Equipment	max. 1,5 mm
Installation mode Connection Conductor cross-section - with screw-in lift terminals for connection to 15-c Equipment - with supporting ring	max. 1,5 mm
Installation mode Connection Conductor cross-section - with screw-in lift terminals for connection to 15-c Equipment	max. 1,5 mm
Installation mode Connection Conductor cross-section - with screw-in lift terminals for connection to 15-c Equipment - with supporting ring Use	max. 1,5 mm
Installation mode Connection Conductor cross-section - with screw-in lift terminals for connection to 15-c Equipment - with supporting ring Use Differentiation characteristic 3 - Sales Identification	max. 1,5 mm core VGA cable with screw-in lift terminal
Installation mode Connection Conductor cross-section - with screw-in lift terminals for connection to 15-c Equipment - with supporting ring Use Differentiation characteristic 3 - Sales	without spreader claws, for screw fastening max. 1,5 mm core VGA cable with screw-in lift terminals Communication technolog Berker S.1/B.3/B.

VGA socket outlet with screw-in lift terminals, Berker S.1/B.3/B.7, polar white matt



Instructions

Information text

For connecting PCs, notebooks, etc. to display devices such as monitors (including LCD monitors) and projectors., Observe the instructions of the cable and device manufacturers for maximum VGA cable lengths!, Fränkische: "Multimedia tube" for laying pre-assembled connection cable, Art. no. 294.10.092, Installation recommendation: Kaiser: "Electronic box" for compliance with the permissible bending radii, Art. No. 1068-02 or 9062-74