



459410



## Aerial socket 4hole single box DC-permeable, Communication technology

### Technical features

### Functions

- Suitable for HDTV

### Connectivity

- remote supply via F-sockets
- with 2 independent SAT outputs (F-sleeves) and 2 IEC outputs (male/female)
- for terrestrial reception
- for digital and analogue transmission

### Voltage

- DC voltage conducting

### Frequency

Broadband technology	5...2400 MHz
----------------------	--------------

### Resistance

Wave impedance	75 Ω
----------------	------

### Attenuation

Tap loss at 2150 MHz	2 dB
Tap loss at 860 MHz	2 dB

### Installation, mounting

- for community and broadband cable systems
- for single and distributor SAT systems
- for multi-switch systems

### Connection

Connection	for simultaneous connection of radio and TV receiver as well as 2 independent SAT receivers
- with screw terminals	

### Settings

- also to add SAT programmes in broadband cable systems

### Equipment

- external eyelets on the supporting ring can be broken off for round designs

### Use

Differentiation characteristic 3 - Sales	DC-permeable
--	--------------

### Standards

General standards	EN 50083-2 and EN 60728-4
-------------------	---------------------------

**Safety**

Protective screen	(VHF/UHF) according to EN 50083-2, Class B, (SAT) according to EN 50083-2, Class A
Protection index IP	IP20

**Use conditions**

Operating temperature	-25...55 °C
-----------------------	-------------

**Identification**

Application, usage	Communication technology
Main design line	Communication technology