



3315411606



VGA socket outlet with screw-in lift terminals, Berker S.1/B.3/B.7, anthracite, matt

Technical features

Architecture

Technical version with screw-in lift terminals

Connectivity

- with straight outlet
- S-VGA compatible
- with 15pole D-subminiature jack (front)

Frequency

Frequency range video max. 160 MHz

Screen

Resolution max. 1280 x 1024 px

Materials

Colour of design line anthracite

Colour anthracite

RAL colour RAL 7021 - Black grey

Material Plastic/metal

Surface appearance matt

Installation, mounting

Installation mode without spreader claws, for screw fastening

Connection

Conductor cross-section max. 1,5 mm²

- with screw-in lift terminals for connection to 15-core VGA cable

Equipment

- with supporting ring

Use

Differentiation characteristic 3 - Sales with screw-in lift terminals

Identification

Application, usage Communication technology

Main design line Berker S.1/B.3/B.7

Secondary design line(s) Berker S.1, Berker B.3, Berker B.7

Instructions

Information text

For connecting PCs, notebooks, etc. to display devices such as monitors (including LCD monitors) and projectors., Observe the instructions of the cable and device manufacturers for maximum VGA cable lengths!, Fränkische: "Multimedia tube" for laying pre-assembled connection cable, Art. no. 294.10.092, Installation recommendation: Kaiser: "Electronic box" for compliance with the permissible bending radii, Art. No. 1068-02 or 9062-74
