



47441949



SCHUKO socket outlet with hinged cover for accessible construction with tactile symbol, enhanced contact protection, Mounting orientation variable in 45° steps, Berker S.1/B.3/B.7, polar white matt

Technical features

Architecture

| | |
|-------------|------------------------|
| Design | according to DIN 49440 |
| Fixing mode | flush-mounting |

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 250 V |
| Rated voltage | 250 V AC |
| Frequency | 50/60 Hz |
| Rated current | 16 A |

Electric current

| | |
|---------------|------|
| Rated current | 16 A |
|---------------|------|

Cover, door

| | |
|-----------------------------------------------------------------|---------------------|
| Cover | Central cover plate |
| - when opening hinged cover, it can be arrested in end position | |

Materials

| | |
|-----------------------|-----------------------|
| Colour of design line | polar white |
| Colour | polarwhite |
| Colour | white |
| RAL colour | RAL 9010 - Pure white |
| Material | thermoplastic |
| Surface appearance | matt |

Dimensions

| | |
|-----------------|-------|
| Insertion depth | 32 mm |
|-----------------|-------|

Installation, mounting

| | |
|-------------------|-----------------------------------------------------------------------------|
| Installation mode | mounting orientation of insert selectable in 45° steps, with spreader claws |
|-------------------|-----------------------------------------------------------------------------|

Connection

| | |
|--------------------------|---------------------------------|
| Connection terminals | according to IEC 60884-1 |
| Connection terminals | according to VDE 0620-1:2021-02 |
| - with plug-in terminals | |

Use cases

| | |
|-----------------------|--------------------|
| Barrier-free building | based on DIN 18040 |
|-----------------------|--------------------|

Use

| | |
|------------------------------------------|--------------------------------------------|
| Differentiation characteristic 1 - Sales | with tactile symbol |
| Differentiation characteristic 2 - Sales | enhanced contact protection |
| Differentiation characteristic 3 - Sales | Mounting orientation variable in 45° steps |

Safety

| | |
|--------------------------------------------------|---------------------------------|
| IK protection code against mechanical impacts | 05 |
| Protection index IP | IP20 |
| Enhanced contact protection | according to IEC 60884-1 |
| Enhanced contact protection | according to VDE 0620-1:2021-02 |
| - enhanced contact protection VDE 0620-1:2021-02 | |

Identification

| | |
|--------------------------|------------------------------------|
| Main design line | Berker S.1/B.3/B.7 |
| Secondary design line(s) | Berker S.1, Berker B.3, Berker B.7 |

Instructions

| | |
|------------------|--------------------------------------------------------------------------------------|
| Information text | Specially suited for combining several socket outlets if right angle plugs are used. |
|------------------|--------------------------------------------------------------------------------------|
