


47506015



**SCHUKO socket outlet with "EDV" imprint Labelling field, Berker Q.1/Q.3/Q.7/Q.9, red velvety**

Technical features

**Architecture**

Design	according to DIN 49440
Fixing mode	flush-mounting
Technical version	Imprint "EDV"

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

**Electric current**

Rated current	16 A
---------------	------

**Cover, door**

Cover	Central cover plate
-------	---------------------

**Materials**

Design lines special colours	red
Colour	red
Colour	red
RAL colour	RAL 3003 - Ruby red
Material	duroplastic
Surface appearance	velvety

**Dimensions**

Insertion depth	32 mm
-----------------	-------

**Installation, mounting**

Installation mode	with spreader claws
-------------------	---------------------

**Connection**

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

**Use**

Differentiation characteristic 1 - Sales	Labelling field
--	-----------------

**Safety**

IK protection code against mechanical impacts	02
Protection index IP	IP20
- without enhanced contact protection	

---

**Identification**

---

Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9

---

**Instructions**

---

Information text	Insert colour-coded., Labelling field height arranged for P-touch strips 6 mm.
------------------	--

---