



47526049



**SCHUKO socket outlet with hinged cover and "ZSV" imprint in orange Labelling field, enhanced contact protection, Berker Q.1/Q.3/Q.7/Q.9, polar white velvety**

Technical features

**Architecture**

Design	according to DIN 49440
Fixing mode	flush-mounting
Technical version	Imprint "ZSV" in orange

**Connectivity**

Type of USB port	other
------------------	-------

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

**Electric current**

Rated current	16 A
---------------	------

**Cover, door**

Cover	Central cover plate
- with self-closing hinged covers	

**Materials**

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	duroplastic
Surface appearance	velvety

**Dimensions**

Insertion depth	32 mm
-----------------	-------

**Installation, mounting**

Installation mode	with spreader claws
-------------------	---------------------

**Connection**

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

**Use**

Differentiation characteristic 1 - Sales	Labelling field
Differentiation characteristic 2 - Sales	enhanced contact protection

### Safety

---

IK protection code against mechanical impacts	02
Protection index IP	IP20
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- enhanced contact protection VDE 0620-1:2021-02	

---

### Identification

---

Application, usage	Flush-mounted wet-room installation
Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9

---

### Instructions

---

Information text	Labelling field height arranged for P-touch strips 6 mm.
- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with the corresponding sealing set.	

---