



47526089



**SCHUKO socket outlet with hinged cover Labelling field, enhanced contact protection, Berker Q.1/Q.3/Q.7/Q.9, polar white velvety**

Technical features

#### Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting

#### Connectivity

Type of USB port	other
------------------	-------

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

#### Electric current

Rated current	16 A
---------------	------

#### Cover, door

Cover	Central cover plate
- with self-closing hinged covers	

#### Materials

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	duroplastic
Surface appearance	velvety

#### Dimensions

Insertion depth	32 mm
-----------------	-------

#### Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

#### Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

#### Use

Differentiation characteristic 1 - Sales	Labelling field
Differentiation characteristic 2 - Sales	enhanced contact protection

### Safety

---

IK protection code against mechanical impacts	02
Protection index IP	IP20
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- enhanced contact protection VDE 0620-1:2021-02	

---

### Identification

---

Application, usage	Flush-mounted wet-room installation
Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9

---

### Instructions

---

Information text	Labelling field height arranged for P-touch strips 6 mm.
- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with sealing set (order no. 10107200).	

---