



47296086 I

# Double SCHUKO socket outlet with cover plate enhanced contact protection, anthracite velvety, lacquered

**Technical features** 

Δ	rch	ite	cti	ıre
_		IILE		uic

Design	according to DIN 49440
Fixing mode	flush-mounting

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

## Electric current

### Cover, door

Cover	Full cover plate
-------	------------------

#### Materials

Colour of design line
Colour
Colour
RAL colour
Material / workmanship
Material
Surface appearance

#### **Dimensions**

Assembling height	22 mm
-------------------	-------

## Installation, mounting

For installation in 1gang wall boxes	according to DIN 49073-1
Installation mode	with spreader claws

#### Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

## Use

Differentiation characteristic 2 - Sales	enhanced contact protection
--	-----------------------------



## Safety

IK protection code against mecanical impacts	02
Protection index IP	IP20
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	
Identification	
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9