



47516076



**SCHUKO socket outlet with hinged cover enhanced contact protection, Berker Q.1/Q.3/Q.7/Q.9, anthracite velvety, lacquered**

Technical features

**Architecture**

|             |                        |
|-------------|------------------------|
| Design      | according to DIN 49440 |
| Fixing mode | flush-mounting         |

**Connectivity**

|                  |       |
|------------------|-------|
| Type of USB port | other |
|------------------|-------|

**Main electrical features**

|                 |          |
|-----------------|----------|
| Nominal voltage | 250 V    |
| Rated voltage   | 250 V AC |
| Frequency       | 50/60 Hz |
| Rated current   | 16 A     |

**Electric current**

|               |      |
|---------------|------|
| Rated current | 16 A |
|---------------|------|

**Cover, door**

|                                     |                     |
|-------------------------------------|---------------------|
| Cover                               | Central cover plate |
| - with hinged cover that falls back |                     |

**Materials**

|                        |                          |
|------------------------|--------------------------|
| Colour of design line  | anthracite               |
| Colour                 | anthracite               |
| Colour                 | anthracite charcoal grey |
| RAL colour             | RAL 7021 - Black grey    |
| Material / workmanship | lacquered                |
| Material               | duroplastic              |
| Surface appearance     | velvety                  |

**Installation, mounting**

|                   |                     |
|-------------------|---------------------|
| Installation mode | with spreader claws |
|-------------------|---------------------|

**Connection**

|                          |                                 |
|--------------------------|---------------------------------|
| Connection terminals     | according to IEC 60884-1        |
| Connection terminals     | according to VDE 0620-1:2021-02 |
| - with plug-in terminals |                                 |

**Use**

|  |                             |
|--|-----------------------------|
| Differentiation characteristic 2 - Sales | enhanced contact protection |
|--|-----------------------------|

---

**Safety**

---

|  |                                 |
|--|---------------------------------|
| IK protection code against mechanical impacts    | 02                              |
| Protection index IP                              | IP20                            |
| Enhanced contact protection                      | according to IEC 60884-1        |
| Enhanced contact protection                      | according to VDE 0620-1:2021-02 |
| - enhanced contact protection VDE 0620-1:2021-02 |                                 |

---

**Identification**

---

|                          |  |
|--------------------------|--|
| Main design line         | Berker Q.1/Q.3/Q.7/Q.9                         |
| Secondary design line(s) | Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9 |

---