



47236086



SCHUKO socket outlet with enhanced touch protection, Berker Q.1/Q.3/Q.7/Q.9, anthracite velvety, lacquered	
Technical features	
Architecture	
Design	according to DIN 49440
Fixing mode	flush-mounting
Connectivity	
Type of USB port	other
Main electrical features	
Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A
Electric current	
Rated current	16 A
Cover, door	
Cover	Central cover plate
Materials	
Colour of design line	anthracite
Colour	anthracite
Colour	anthracite charcoal grey
RAL colour	RAL 7021 - Black grey
Material / workmanship	lacquered
Material	duroplastic
Surface appearance	velvety
Dimensions	
Insertion depth	32 mm
Installation depth, flush-mounted boxes	31 mm
Installation, mounting	
Installation mode	with spreader claws
Connection	
Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	
Use	
Differentiation characteristic 2 - Sales	with enhanced touch protection

Safety

IK protection code against mechanical impacts	02
Protection index IP	IP20
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	

Identification

Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9