




41686086



**Socket outlet with earthing contact USA/CANADA NEMA 5-20 R with screw terminals, Berker Q.1/Q.3/Q.7/Q.9, anthracite velvety, lacquered**

Technical features

**Architecture**

Fixing mode	flush-mounting
- 2pole + earth	

**Main electrical features**

Nominal voltage	125 V
Rated voltage	125 V AC
Frequency	50/60 Hz
Rated current	20 A

**Cover, door**

Cover	Central cover plate
-------	---------------------

**Materials**

Colour of design line	anthracite
Colour	anthracite
Colour	anthracite charcoal grey
RAL colour	RAL 7021 - Black grey
Material / workmanship	lacquered
Material	thermoplastic
Surface appearance	velvety

**Dimensions**

Insertion depth	19 mm
-----------------	-------

**Installation, mounting**

Installation mode	without spreader claws, for screw fastening
-------------------	---

**Connection**

Conductor cross-section (rigid)	max. 2 x 4 mm <sup>2</sup>
- with screw terminals	

**Use**

Differentiation characteristic 3 - Sales	with screw terminals
--	----------------------

**Standards**

Standard	NEMA 5-20 R
----------	-------------

**Safety**

IK protection code against mechanical impacts	05
- without enhanced contact protection	

**Identification**

Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9

**Instructions**

Information text	Not UL-certified.
------------------	-------------------