



16216076



Rocker with imprinted symbol for light Lens, Berker Q.1/Q.3/Q.7/Q.9, anthracite velvety, lacquered

Technical features

Controls and indicators

- also for KNX applications: push-button, 1 gang, and group push-button, 1 gang
- for rocker push-buttons
- for change-over/intermediate switch

Materials

| | |
|------------------------|--------------------------|
| Colour of design line | anthracite |
| Colour | anthracite |
| Colour | anthracite charcoal grey |
| RAL colour | RAL 7021 - Black grey |
| Material / workmanship | lacquered |
| Material | duroplastic |
| Surface appearance | velvety |

Installation, mounting

| | |
|-------------------|-----------------|
| Installation mode | clamp fastening |
|-------------------|-----------------|

Equipment

- for lighting and monitoring circuit

Use

| | |
|--|------|
| Differentiation characteristic 2 - Sales | Lens |
|--|------|

Identification

| | |
|--------------------------|--|
| Application, usage | Light control, Flush-mounted wet-room installation, KNX radio- operating systems |
| Main design line | Berker Q.1/Q.3/Q.7/Q.9 |
| Secondary design line(s) | Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9 |

Instructions

- The IP44 degree of protection can only be achieved in conjunction with the appropriate neon, incandescent or LED lamp unit, as well as a sealing set for switches/push-buttons.