



### 16286086







## Rocker with labelling field, Lens, Berker Q.1/Q.3/Q.7/Q.9, anthracite velvety, lacquered

Technical features

#### **Controls and indicators**

- also for KNX applications: push-button, 1gang, and group push-button, 1gang
- for rocker push-buttons
- for change-over/intermediate switch

#### Materials

anthracite
anthracite
anthracite charcoal grey
RAL 7021 - Black grey
lacquered
duroplastic
velvety

## Installation, mounting

Installation mode clamp fastening

## Equipment

- for lighting and monitoring circuit

### Use

Differentiation characteristic 1 - Sales with labelling field
Differentiation characteristic 2 - Sales Lens

# Identification

Application, usage	Flush-mounted wet-room installation, Light control,
	KNX - operating systems
Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9

# Instructions

Information text

For labelling with names, notes etc.

- The IP44 degree of protection can only be achieved in confidential field by the particular feeting and feeting protection and only be achieved in confidential field by the particular feeting protection and protection can only be achieved in confidential field by the particular feeting protection can only be achieved in confidential field by the particular feeting feetin