



6765106089





Socket outlet with earthing pin and LED orientation light enhanced contact protection, Screw-in lift terminals, Berker Q.1/Q.3/Q.7/Q.9, polar white velvety

Technical features

e

Fixing mode	flush-mounting
- 2pole + earth	

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Power

Power consumption	0.25 W/0.35 VA
-------------------	----------------

Cover, door

Cover	Central cover plate
COVEI	Certifial Cover blate

Detection

 integrated brightness sensor that switches the orientation light on at twilight and off when there is sufficient brightness

Materials

polar white	Colour of design line
polarwhite	Colour
white	Colour
RAL 9010 - Pure white	RAL colour
thermoplastic	Material
velvety	Surface appearance

Dimensions

Insertion depth	32 mm
-----------------	-------

Lighting control

Switch-off brightness	≈ 4 lx
Switch-on brightness	≈ 2 lx
Light intensity (white)	0,2 cd

LED control

Installation, mounting

Installation mode with spreade	er claw	S
--------------------------------	---------	---



necti	

Conductor cross-section (rigid)	max. 2,5 mm²
Connection terminals	according to IEC 60884-1
- with screw-in lift terminals	

Cable

- through-wiring possible, therefore also ideal for retrofitting

Equipment

- additional benefit by combination of a socket outlet with an orientation light

Use

Differentiation characteristic 2 - Sales	enhanced contact protection
Differentiation characteristic 3 - Sales	Screw-in lift terminals

Safety

IK protection code against mecanical impacts	05
Enhanced contact protection	according to IEC 60884-1
- Enhanced contact protection	

Identification

Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9

Instructions

Caution!
Items with special flush-mounted insert.
Centre plates with LED orientation lights are not
compatible with the standard socket outlets.