



16616049



Rocker for accessible construction with guide for mouth-held rod, Lens, Berker Q.1/Q.3/Q.7/Q.9, polar white velvety

Technical features

Controls and indicators

- also for KNX applications: push-button, 1 gang, and group push-button, 1 gang
- for change-over/intermediate switch
- for rocker push-buttons

Materials

| | |
|-----------------------|-----------------------|
| Colour of design line | polar white |
| Colour | polarwhite |
| Colour | white |
| RAL colour | RAL 9010 - Pure white |
| Material | duroplastic |
| Surface appearance | velvety |

Installation, mounting

| | |
|-------------------|-----------------|
| Installation mode | clamp fastening |
|-------------------|-----------------|

Equipment

- for lighting and monitoring circuit

Use cases

| | |
|-----------------------|--------------------|
| Barrier-free building | based on DIN 18040 |
|-----------------------|--------------------|

Use

| | |
|--|-------------------------------|
| Differentiation characteristic 1 - Sales | with guide for mouth-held rod |
| Differentiation characteristic 2 - Sales | Lens |

Identification

| | |
|--------------------------|--|
| Application, usage | Flush-mounted wet-room installation |
| Main design line | Berker Q.1/Q.3/Q.7/Q.9 |
| Secondary design line(s) | Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9 |

Instructions

- The IP44 degree of protection can only be achieved in conjunction with the appropriate neon, incandescent or LED lamp unit, as well as a sealing set for switches/push-buttons.