





IP20

### SCHUKO socket outlet with screw-in lift terminals, Berker K.1, polar white glossy

**Technical features** 

AICHILECTULE	Arc	hite	cture
--------------	-----	------	-------

Design	according to DIN 49440
Fixing mode	flush-mounting

### Connectivity

Type of USB port	other

### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

#### **Electric current**

Rated current	16 A

#### Cover, door

Cover	Central cover plate
-------	---------------------

#### Materials

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	glossy

### **Dimensions**

Insertion depth	32 mm
Installation depth, flush-mounted boxes	31 mm

### Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

#### Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with screw-in lift terminals	

# Use

Differentiation characteristic 3 - Sales	with screw-in lift terminals
Differentiation characteristic 3 - Sales	With Sciew-III III terrilliais



## Safety

IK protection code against mecanical impacts	05
Protection index IP	IP20
- without enhanced contact protection	
Identification	
Main design line	Berker K.1