



47517106



**SCHUKO socket outlet with hinged cover enhanced contact protection, Berker K.1, anthracite matt, lacquered**

Technical features

**Architecture**

Design	according to DIN 49440
Fixing mode	flush-mounting

**Connectivity**

Type of USB port	other
------------------	-------

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

**Electric current**

Rated current	16 A
---------------	------

**Cover, door**

Cover	Central cover plate
- when opening hinged cover, it can be arrested in end position	

**Materials**

Colour of design line	anthracite
Colour	anthracite
Colour	anthracite charcoal grey
RAL colour	RAL 7021 - Black grey
Material / workmanship	lacquered
Material	thermoplastic
Surface appearance	matt

**Installation, mounting**

Installation mode	with spreader claws
-------------------	---------------------

**Connection**

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

**Use**

Differentiation characteristic 2 - Sales	enhanced contact protection
--	-----------------------------

---

**Safety**

---

IK protection code against mechanical impacts	05
Protection index IP	IP20
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- enhanced contact protection VDE 0620-1:2021-02	

---

**Identification**

---

Main design line	Berker K.1
------------------	------------

---