



47527106



**SCHUKO socket outlet with hinged cover Labelling field, enhanced contact protection, Berker K.1, anthracite matt, lacquered**

Technical features

### Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting

### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

### Electric current

Rated current	16 A
---------------	------

### Cover, door

Cover	Central cover plate
- when opening hinged cover, it can be arrested in end position	

### Materials

Colour of design line	anthracite
Colour	anthracite
Colour	anthracite charcoal grey
RAL colour	RAL 7021 - Black grey
Material / workmanship	lacquered
Material	thermoplastic
Surface appearance	matt

### Dimensions

Insertion depth	32 mm
-----------------	-------

### Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

### Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

### Use

Differentiation characteristic 1 - Sales	Labelling field
Differentiation characteristic 2 - Sales	enhanced contact protection

---

**Safety**

---

IK protection code against mechanical impacts	05
Protection index IP	IP20
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	

---

**Identification**

---

Main design line	Berker K.1
------------------	------------

---

**Instructions**

---

Information text	Labelling field height arranged for 6 mm P-touch strips.
	Specially suited to combinations of several socket outlets if right angle plugs are used.

---