



41527115



**SCHUKO socket outlet with overvoltage protection with labelling field, Screw terminals, Berker K.1, red glossy**

Technical features

### Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting

### Controls and indicators

- with acoustic fault signal

### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

### Voltage

Overvoltage protection	according to EN 61643 and VDE 0675-6-11
------------------------	---

### Electric current

Rated current	16 A
---------------	------

### Cover, door

Cover	Central cover plate
-------	---------------------

### Materials

Colour of design line	red
Design lines special colours	red
Colour	red
Colour	red
RAL colour	RAL 3003 - Ruby red
Material	thermoplastic
Surface appearance	glossy

### Dimensions

Insertion depth	32 mm
-----------------	-------

### Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

### Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with screw terminals	

### Equipment

- with indicator LED for On/Error

---

**Use**

---

Differentiation characteristic 1 - Sales	with labelling field
Differentiation characteristic 3 - Sales	Screw terminals

---

**Safety**

---

IK protection code against mechanical impacts	07
Protection index IP	IP20
- without enhanced contact protection	

---

**Identification**

---

Main design line	Berker K.1
------------------	------------

---

**Instructions**

---

Information text	Insert colour-coded. 1140.
	Labelling field height designed for 6 mm P-touch strips.

---