
product sheet 20347109







| - with on/off switch and 2 LEDs | |
|--|---|
| Main electrical features | |
| Nominal voltage | 230 |
| Rated voltage | 230 V A0 |
| Frequency | 50/60 H: |
| Electric current | |
| Switching current | 10 / |
| Materials | |
| Colour of design line | polar white |
| Colour | polarwhite |
| Material | Plastic/meta |
| LED control | |
| LED | with LED for heating and LED for night lowering |
| Installation, mounting | |
| Installation mode | without spreader claws |
| Connection | |
| Sensor cable length | 4 n |
| Connection | with separate connection for night lowering |
| - with plug-in terminals | |
| Settings | |
| Floor temperature setting range | 1050 °C |
| Room temperature setting range | 530 °C |
| Equipment | |
| Night lowering | ≈ 5 H |
| Switching temperature difference | ≈1⊦ |
| setting knob with temperature range limitation e.g. for valve drives closed in de-energised state | |
| Use | |
| Differentiation characteristic 1 - Sales | with rocker switch |
| Differentiation characteristic 3 - Sales | external temperature senso |
| Use conditions | |
| Energy efficiency class | I (1% |
| - with thermal return | 、 |

Thermostat, NO contact, with centre plate, for underfloor heating with rocker switch, external temperature sensor, Berker K.1, polar white glossy



Identification

| Application, usage | HVAC control |
|--------------------|--------------|
| Main design line | Berker K.1 |