



85241173



IP20

Blind button Berker K.5, stainless steel matt, lacquered

Technical features

Functions

Venetian blind movement time	2 mn
------------------------------	------

- Memory function for automatic execution of learned up and down times with position
- Party function, no execution of automatic, radio and extension unit commands (lock-out protection)

Controls and indicators

- activation of the party function using buttons in up and down direction > 20 sec.

Main electrical features

Nominal voltage	12 V
-----------------	------

Frequency	- Hz
-----------	------

Measurement

Relative humidity (without condensation)	0...65 % (without condensation)
--	---------------------------------

Detection

- Not suitable for rain and wind sensors

Materials

Colour of design line	stainless steel
-----------------------	-----------------

Colour	stainless steel
--------	-----------------

Material / workmanship	lacquered
------------------------	-----------

Material	thermoplastic
----------	---------------

LED control

LED	LED application module/insert compatibility display, with status LED for memory and party function, red/orange, with indicator LED for lock-out protection
-----	--

Installation, mounting

Installation mode	clamp fastening
-------------------	-----------------

Settings

Lamella adjusting time	(adjustable) 50 ms...2,5 s
------------------------	----------------------------

Minimum slat adjustment time	≈ 250 ms
------------------------------	----------

Delay time, adjustable	0...500 s
------------------------	-----------

Lamella adjustment on button-press	< 0,4 s
------------------------------------	---------

Equipment

Self-retaining for 2 min on button-press	> 0,4 s
--	---------

Change-over time for change of direction	< 0,6 s
--	---------

Safety

- with dismantling protection

Use conditions

Operating temperature	-5...45 °C
- low intrinsic energy requirement	

Identification

Application, usage	Blind control
Main design line	Berker K.5
Secondary design line(s)	Electronics platform, Berker K.5

Instructions

- Can be switched to orientation led by extension unit.