


47527204



**SCHUKO socket outlet with hinged cover Labelling field, enhanced contact protection, Berker K.5, stainless steel, metal matt finish**

Technical features

#### Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

#### Electric current

Rated current	16 A
---------------	------

#### Cover, door

Cover	Central cover plate
-	with self-closing hinged covers

#### Materials

Colour of design line	Stainless steel
Colour	stainless steel
Colour	stainless steel optics
RAL colour	RAL 9022 - Pearl light grey
Material / workmanship	metal, matt finish
Material	stainless steel
Surface appearance	matt

#### Dimensions

Insertion depth	32 mm
-----------------	-------

#### Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

#### Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
-	with plug-in terminals

#### Use

Differentiation characteristic 1 - Sales	Labelling field
Differentiation characteristic 2 - Sales	enhanced contact protection

### Safety

IK protection code against mechanical impacts	07
Protection index IP	IP44
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	

### Identification

Application, usage	Flush-mounted wet-room installation
Main design line	Berker K.5

### Instructions

Information text	Labelling field height arranged for 6 mm P-touch strips.
------------------	--

- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with sealing set (order no. 10107200). Specially suited to combinations of several socket outlets if right angle plugs are used.