# product sheet 47280001



47280001

**Technical features** 

| Design      | according to DIN 49440 |
|-------------|------------------------|
| Fixing mode | flush-mounting         |

#### Main electrical features

| Nominal voltage | 250 V    |
|-----------------|----------|
| Rated voltage   | 250 V AC |
| Frequency       | 50/60 Hz |
| Rated current   | 16 A     |

### **Electric current**

| Rated current | 16 A |
|---------------|------|
|               |      |

# Cover, door

|  | Central cover plate |
|--|---------------------|
|--|---------------------|

## Materials

Cover

| Colour of design line | brown                |
|-----------------------|----------------------|
| Colour                | brown                |
| Colour                | brown                |
| RAL colour            | RAL 8011 - Nut brown |
| Material              | duroplastic          |
| Surface appearance    | glossy               |

### Dimensions

Insertion depth

### Installation, mounting

| Installation mode        | with spreader claws |
|--------------------------|---------------------|
| - for diagonal insertion |                     |

#### Connection

| Connection terminals     | according to IEC 60884-1        |
|--------------------------|---------------------------------|
| Connection terminals     | according to VDE 0620-1:2021-02 |
| - with plug-in terminals |                                 |

#### Safety

| IK protection code against mecanical impacts | 02   |
|--|------|
| Protection index IP                          | IP20 |
| - without enhanced contact protection        |      |

## Identification

| Main design | line |
|-------------|------|
|-------------|------|

Berker Arsys

32 mm



#### Instructions

Information text

Specially suited for combining several socket outlets if right angle plugs are used.