product sheet 47380063



47380063



Architecture	
Design	according to DIN 4944
Fixing mode	flush-mounting
Connectivity	
Type of USB port	othe
Main electrical features	
Nominal voltage	250 \
Rated voltage	250 V A
Frequency	50 H
Rated current	167
Electric current Rated current	16.4
	107
Cover, door	
Cover	Central cover plat
Materials	
Design lines special colours	greei
Colour	greer
RAL colour	RAL 6029 - Mint gree
Material	duroplastic
Surface appearance	gloss
Dimensions	
Installation depth, flush-mounted boxes	32 mn
Connection	
Connection terminals	according to IEC 60884-
Connection terminals	according to VDE 0620-1:2021-0:
- with plug-in terminals	
Use	
Differentiation characteristic 1 - Sales	with labelling field
Differentiation characteristic 2 - Sales	enhanced contact protectio
Safety	
IK protection code against mecanical impacts	0
Protection index IP	IP2
Enhanced contact protection	according to IEC 60884-
Enhanced contact protection	according to VDE 0620-1:2021-0
- Enhanced contact protection	-

SCHUKO socket outlet with labelling field, enhanced contact protection, Berker Arsys, green glossy



mm.

Identification	
Main design line	Berker Arsys
Instructions	
Information text	Labelling field height arranged for P-touch strips 6