



41520069







SCHUKO socket outlet with overvoltage protection with labelling field, Screw terminals, Berker Arsys, polar white glossy

**Technical features** 

# Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting

### **Controls and indicators**

- with acoustic fault signal

### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

#### Voltage

Overvoltage protection according to EN 61643 and VDE 0675-6-11

#### **Electric current**

Rated current 16 A

### Cover, door

Cover Central cover plate

#### Materials

polar white	
polarwhite	
white	
RAL 9010 - Pure white	
duroplastic	
glossy	

## **Dimensions**

Insertion depth 32 mm

# Installation, mounting

Installation mode with spreader claws

# Connection

Connection terminals according to IEC 60884-1

Connection terminals according to VDE 0620-1:2021-02

- with screw terminals

## **Equipment**

- with indicator LED for On/Error



_	3	c

Differentiation characteristic 1 - Sales	with labelling field	
Differentiation characteristic 3 - Sales	Screw terminals	
Safety		
IK protection code against mecanical impacts	02	
Protection index IP	IP20	
- without enhanced contact protection		
Identification		
Main design line	Berker Arsys	
Instructions		
Information text	Labelling field height arranged for P-touch strips 6 mm.	