



47583004



**SCHUKO socket outlet with hinged cover enhanced contact protection, Berker Arslys IP44, stainless steel, metal matt finish**

Technical features

### Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting

### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

### Electric current

Rated current	16 A
---------------	------

### Cover, door

Cover	Central cover plate
-------	---------------------

### Materials

Colour of design line	Stainless steel
Colour	stainless steel
Colour	stainless steel optics
RAL colour	RAL 9022 - Pearl light grey
Material / workmanship	metal, matt finish
Material	stainless steel
Surface appearance	matt

### Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

### Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

### Use

Differentiation characteristic 2 - Sales	enhanced contact protection
--	-----------------------------

### Safety

IK protection code against mechanical impacts	07
Protection index IP	IP20
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	

---

**Identification**

---

Application, usage	Flush-mounted wet-room installation
Main design line	Berker Arsys IP44

---

**Instructions**

- 
- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with sealing set (order no. 101000).
-