



10300069

Frame 2gang surface-mounted Surface-mounted accessories, polar white glossy

Technical features

| • | | | | | | | |
|---|----|---|----|---|----|----|---|
| Λ | rc | n | 11 | 2 | 11 | IP | 0 |
| | | | | | | | |

| Technical version | 2gang |
|-------------------|-------|
| | |

Materials

| of design line | polar white |
|-------------------|-----------------------|
| | polarwhite |
| | white |
| our | RAL 9010 - Pure white |
| | duroplastic |
| appearance | glossy |
| surface treatment | untreated |

Dimensions

| Depth | 35 mm |
|-----------------|---------|
| Insertion depth | 33,5 mm |
| Height | 85 mm |
| Width | 155 mm |

Installation, mounting

| Installation mode | | for vertical and horizontal mounting |
|-------------------|--------------|--------------------------------------|
| | 1.0 1 11 111 | |

- entry at top, bottom and 2 x each side possible

Cable

- with line and duct entry

Safety

| Protection index IP | IP20 |
|---------------------|------|
|---------------------|------|

Identification

| Main design line | Surface-mounted accessories |
|------------------|-----------------------------|
| Main acsign inic | Surface mounted accessories |

Instructions

| Information text | For matching pipe lead-ins and replacement for cable and duct entries, refer to the chapter Dry |
|------------------|---|
| | surface-mounted installation. |