



6768760063



## Socket outlet with earthing pin with enhanced touch protection, Berker S.1/B.3/B.7, green matt

### Technical features

#### Architecture

Fixing mode	flush-mounting
- 2pole + earth	

#### Connectivity

Type of USB port	other
------------------	-------

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

#### Cover, door

Cover	Central cover plate
-------	---------------------

#### Materials

Design lines special colours	green
Colour	green
Colour	green
RAL colour	RAL 6029 - Mint green
Material	thermoplastic
Surface appearance	matt

#### Dimensions

Insertion depth	32 mm
Installation depth, flush-mounted boxes	31 mm
Mirror depth	14,5 mm

#### Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

#### Connection

Connection terminals	according to IEC 60884-1
- with plug-in terminals	

#### Use

Differentiation characteristic 2 - Sales	with enhanced touch protection
--	--------------------------------

#### Safety

IK protection code against mechanical impacts	05
Enhanced contact protection	according to IEC 60884-1
- Enhanced contact protection	

**Identification**

---

Main design line	Berker S.1/B.3/B.7
Secondary design line(s)	Berker S.1, Berker B.3, Berker B.7

---

**Instructions**

---

Information text	Insert colour-coded.
------------------	----------------------

---