



52048989



## Mains adapter with frame Berker S.1, polar white glossy

### Technical features

#### Main electrical features

|           |          |
|-----------|----------|
| Frequency | 50-60 Hz |
|-----------|----------|

#### Voltage

|               |                |
|---------------|----------------|
| Input voltage | 100...240 V AC |
|---------------|----------------|

|                |         |
|----------------|---------|
| Output voltage | 24 V DC |
|----------------|---------|

#### Electric current

|               |             |
|---------------|-------------|
| Input current | max. 180 mA |
|---------------|-------------|

|                |             |
|----------------|-------------|
| Output current | max. 250 mA |
|----------------|-------------|

#### Materials

|                       |             |
|-----------------------|-------------|
| Colour of design line | polar white |
|-----------------------|-------------|

|        |            |
|--------|------------|
| Colour | polarwhite |
|--------|------------|

|        |       |
|--------|-------|
| Colour | white |
|--------|-------|

|            |                       |
|------------|-----------------------|
| RAL colour | RAL 9010 - Pure white |
|------------|-----------------------|

|                    |        |
|--------------------|--------|
| Surface appearance | glossy |
|--------------------|--------|

#### Installation, mounting

|                                         |                          |
|-----------------------------------------|--------------------------|
| For installation in standard wall boxes | according to DIN 49073-1 |
|-----------------------------------------|--------------------------|

|                   |                                 |
|-------------------|---------------------------------|
| Installation mode | centre plate for plug-in fixing |
|-------------------|---------------------------------|

#### Connection

|                        |  |
|------------------------|--|
| - with screw terminals |  |
|------------------------|--|

#### Use conditions

|                       |            |
|-----------------------|------------|
| Operating temperature | -5...40 °C |
|-----------------------|------------|

#### Identification

|                  |            |
|------------------|------------|
| Main design line | Berker S.1 |
|------------------|------------|

#### Instructions

|                  |                               |
|------------------|-------------------------------|
| Information text | Recommendation: use deep box. |
|------------------|-------------------------------|