



### 3gang SCHUKO socket outlet with cover plate Berker S.1, anthracite matt

#### Technical features

#### Architecture

|             |                        |
|-------------|------------------------|
| Design      | according to DIN 49440 |
| Fixing mode | flush-mounting         |

#### Main electrical features

|                 |          |
|-----------------|----------|
| Nominal voltage | 250 V    |
| Rated voltage   | 250 V AC |
| Frequency       | 50 Hz    |
| Rated current   | 16 A     |

#### Electric current

|               |      |
|---------------|------|
| Rated current | 16 A |
|---------------|------|

#### Cover, door

|       |                  |
|-------|------------------|
| Cover | Full cover plate |
|-------|------------------|

#### Materials

|                       |                          |
|-----------------------|--------------------------|
| Colour of design line | anthracite               |
| Colour                | anthracite charcoal grey |
| RAL colour            | RAL 7021 - Black grey    |
| Material              | thermoplastic            |
| Surface appearance    | matt                     |

#### Installation, mounting

|                   |                        |
|-------------------|------------------------|
| Installation time | ≈ 2 mn                 |
| Installation mode | without spreader claws |

#### Connection

|                          |                                 |
|--------------------------|---------------------------------|
| Conductor cross-section  | 2,5 mm <sup>2</sup>             |
| Connection terminals     | according to IEC 60884-1        |
| Connection terminals     | according to VDE 0620-1:2021-02 |
| - with plug-in terminals |                                 |

#### Cable

|                           |       |
|---------------------------|-------|
| Pre-assembled cables      | ≈ 1 m |
| - through-wiring possible |       |

#### Scope of delivery

|                                  |  |
|----------------------------------|--|
| - common base, connected-through |  |
|----------------------------------|--|

#### Accessories included

|                    |  |
|--------------------|--|
| - without wall box |  |
|--------------------|--|

47661949



**Safety**

---

|   |      |
|---|------|
| IK protection code against mechanical impacts | 05   |
| Protection index IP                           | IP20 |
| - without enhanced contact protection         |      |

---

**Identification**

---

|                  |            |
|------------------|------------|
| Main design line | Berker S.1 |
|------------------|------------|

---