



16408984



## Relay switch with centre plate for hotel card Berker S.1/B.3/B.7, aluminium matt

### Technical features

#### Architecture

Fixing mode	flush-mounting
-------------	----------------

#### Configuration

- 1pole
---------

#### Main electrical features

Nominal voltage	230 V
Rated voltage	230 V AC
Frequency	50/60 Hz

#### Electric current

Inductive load at $\cos \varphi = 0.6$	max. 6 A
Switching current	10 A / 230 V AC1

#### Power

Conventional transformers	1500 VA
Electronic transformers	1500 W
Power consumption	< 0.2 W

#### Materials

Colour of design line	aluminium
Colour	aluminium
Colour	aluminium optics
RAL colour	RAL 9006 - White aluminium
Material	Plastic/metal
Surface appearance	matt

#### Dimensions

Depth	57,3 mm
Insertion depth	32 mm
Card width	max. 55 mm
Card thickness	0,8...1,2 mm
Height	71 mm
Width	71 mm

#### Fluorescent bulbs control

Compact fluorescent lamps	500 W
Fluorescent lamps in duo circuit	1500 W

#### LED control

LED	illuminated with blue LED if hotel card is not inserted
-----	---

#### Incandescent bulbs control

230 V incandescent lamps and halogen lamps	1500 W
--	--------

#### Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

#### Connection

Screw terminals (max.)	2 x 2,5 mm <sup>2</sup>
- with screw-in lift terminals	

#### Settings

Delay time incrementally adjustable	0, 15, 30, 60 s
- with potentiometer for incremental adjustment of delay time	

#### Equipment

- for illumination
- with potential-free contact

#### Safety

Protection index IP	IP20
---------------------	------

#### Use conditions

Operating temperature	-5...50 °C
Storage/transport temperature	-25...70 °C (storage at > 45°C reduces the service life)

#### Identification

Application, usage	Light control
Main design line	Berker S.1/B.3/B.7
Secondary design line(s)	Berker S.1, Berker B.3, Berker B.7