



6161036084



## Socket outlet without earthing contact with screw terminals, Berker Q.1/Q.3/Q.7/Q.9

### Technical features

#### Architecture

Fixing mode	flush-mounting
- 2pole	

#### Connectivity

Type of USB port	other
------------------	-------

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

#### Cover, door

Cover	Central cover plate
-------	---------------------

#### Materials

Colour of design line	aluminium
Colour	aluminium
Colour	aluminium optics
RAL colour	RAL 9006 - White aluminium
Material / workmanship	lacquered
Material	duroplastic
Surface appearance	velvety

#### Dimensions

Insertion depth	32 mm
Installation depth, flush-mounted boxes	31 mm
Mirror depth	8 mm

#### Installation, mounting

Installation mode	for screw fastening
-------------------	---------------------

#### Connection

Connection terminals	according to IEC 60884-1
- with screw terminals	

#### Use

Differentiation characteristic 3 - Sales	with screw terminals
--	----------------------

#### Safety

IK protection code against mechanical impacts	02
- without enhanced contact protection	

**Identification**

---

Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9

---