



47516089





SCHUKO socket outlet with hinged cover enhanced contact protection, Berker Q.1/Q.3/Q.7/Q.9, polar white velvety

Technical features

Arc		

Design	according to DIN 49440
Fixing mode	flush-mounting

Connectivity

Type of USB port	other

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16.	Α

Cover, door

Cover	Central cover plate
- with self-closing hinged covers	

Materials

polar white
polarwhite
white
RAL 9010 - Pure white
duroplastic
velvety

Installation, mounting

Installation mode	with spreader claws

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

Use

Differentiation characteristic 2 - Sales	enhanced contact protection
--	-----------------------------



Safety

IK protection code against mecanical impacts	02
Protection index IP	IP20
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	

Identification

Application, usage	Flush-mounted wet-room installation
Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9

Instructions

- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with sealing set (order no. 10107200).