



41681909



Socket outlet with earthing contact USA/CANADA NEMA 5-20 R with screw terminals, Berker S.1/B.3/B.7, polar white matt, lacquered

Technical features

Arc		

Fixing mode	flush-mounting
- 2pole + earth	

Main electrical features

Nominal voltage	125 V
Rated voltage	125 V AC
Frequency	50/60 Hz
Rated current	20 A

Cover, door

Central cover plate

Materials

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material / workmanship	lacquered
Material	thermoplastic
Surface appearance	matt

Dimensions

Insertion depth	19 mm
-----------------	-------

Installation, mounting

Installation mode	without spreader claws, for screw fastening
-------------------	---

Connection

Conductor cross-section (rigid)	max. 2 x 4 mm ²
- with screw terminals	

Use

Differentiation characteristic 3 - Sales	with screw terminals
--	----------------------

Standards

Standard	NEMA 5-20 R
----------	-------------

Safety

IK protection code against mecanical impacts	05
- without enhanced contact protection	



Identification

Main design line	Berker S.1/B.3/B.7	
Secondary design line(s)	Berker S.1, Berker B.3, Berker B.7	
Instructions		
Information text	Not UL-certified.	