



**LED unit 230 V, for switches/push-buttons Light control, white**

Technical features

**Architecture**

|                   |                |
|-------------------|----------------|
| Fixing mode       | flush-mounting |
| Technical version | 230 V~, 1 mA   |

**Controls and indicators**

- for rocker push-buttons and multiple rockers push-buttons, except order no. 503404, 503808
- for change-over/intermediate switch and on/off switch, 2-pole, 10 AX

**Main electrical features**

|               |      |
|---------------|------|
| Rated current | 1 mA |
|---------------|------|

**Endurance**

|                         |            |
|-------------------------|------------|
| Service life of the LED | ≈ 100000 h |
|-------------------------|------------|

**Materials**

|                                    |                         |
|------------------------------------|-------------------------|
| Colour independent of design lines | white                   |
| RAL colour                         | RAL 1013 - Oyster white |

**Equipment**

- for lighting and monitoring circuit
- for series switch illuminated

**Identification**

|                          |  |
|--------------------------|--|
| Application, usage       | Surface-mounted wet-room installation, Light control |
| Main design line         | Light control  |
| Secondary design line(s) | Light control, ACCESSORIES                           |

**Instructions**

|                  |   |
|------------------|---|
| Information text | When several LED units are used, the LED current may result in malfunctioning of the relay/pulse relay.<br>Remedy: Carry along a neutral conductor or connect a capacitor 230 V (1 µF per 10 mA LED current) in parallel with the coil. |
|                  | - Refer to the overview for the matching flush-mounted inserts.   |
|                  | - these marked articles (see symbol) are only suitable for the water-protected flush-mounted installation IP44 in conjunction with the corresponding seal, frame and contact protection box (imprint "IP44").                           |

1686

