



29528989



LED signal light, red/green lighting Berker S.1/B.3/B.7, polar white glossy

Technical features

Architecture

| | |
|-------------|----------------|
| Fixing mode | flush-mounting |
|-------------|----------------|

Main electrical features

| | |
|---------------|----------|
| Rated voltage | 230 V AC |
|---------------|----------|

| | |
|-----------|----------|
| Frequency | 50/60 Hz |
|-----------|----------|

Power

| | |
|-------------------|---|
| Power consumption | at 230 ~, 50 Hz - per colour max. 0,5 W |
|-------------------|---|

Materials

| | |
|-----------------------|-------------|
| Colour of design line | polar white |
|-----------------------|-------------|

| | |
|--------|------------|
| Colour | polarwhite |
|--------|------------|

| | |
|--------|-------|
| Colour | white |
|--------|-------|

| | |
|------------|-----------------------|
| RAL colour | RAL 9010 - Pure white |
|------------|-----------------------|

| | |
|----------|---------------|
| Material | Plastic/metal |
|----------|---------------|

| | |
|--------------------|--------|
| Surface appearance | glossy |
|--------------------|--------|

LED control

| | |
|--------------------|---|
| Quantity LED lamps | 4 |
|--------------------|---|

Installation, mounting

| | |
|---|--------------------------|
| For installation in standard wall boxes | according to DIN 49073-1 |
|---|--------------------------|

Connection

| | |
|-------------------------|---------------------|
| Conductor cross-section | 2,5 mm ² |
|-------------------------|---------------------|

Equipment

- switchable between red and green via separate switches

temperatur

| | |
|---------------------|------------|
| Ambient temperature | -5...40 °C |
|---------------------|------------|

Identification

| | |
|------------------|--------------------|
| Main design line | Berker S.1/B.3/B.7 |
|------------------|--------------------|

| | |
|--------------------------|------------------------------------|
| Secondary design line(s) | Berker S.1, Berker B.3, Berker B.7 |
|--------------------------|------------------------------------|