



383620



**Change-over switch for lock cylinders with earth contact, Splash-protected flush-mounted IP44**

Technical features

**Architecture**

Type of control unit	Key
Fixing mode	surface-mounting

**Configuration**

- Off/change-over

**Controls and indicators**

- No

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC

**Electric current**

Switching current	16 AX (200 W Self Ballasted Lamp (SBL))
-------------------	---

**Materials**

Material	Plastic/metal
----------	---------------

**Dimensions**

Depth	40,2 mm
Height	71 mm
Width	71 mm

**Installation, mounting**

Installation mode	without spreader claws, for screw fastening
-------------------	---

**Connection**

Connection terminals	according to IEC 60669-1
Connection terminals	according to VDE 0632-1
Type of connection	Screw connection
- with screw terminals	

**Equipment**

- for master-key systems
- for lock cylinder

**Use**

Differentiation characteristic 2 - Sales	with earth contact
--	--------------------

**Safety**

Protection index IP	IP44
---------------------	------

**Identification**

---

Application, usage	Light control
Main design line	Splash-protected flush-mounted IP44

---

**Instructions**

---

Information text	for standardised profile half-cylinder lock, 40 mm
------------------	--

---