



41686089



Socket outlet with earthing contact USA/CANADA NEMA 5-20 R with screw terminals, Berker Q.1/Q.3/Q.7/Q.9, polar white velvety

Technical features

Arc	hi	te	cti	ure	2

Fixing mode	flush-mounting
- 2pole + earth	

Main electrical features

Nominal voltage	125 V
Rated voltage	125 V AC
Frequency	50/60 Hz
Rated current	20 A

Cover, door

Cover	Central cover plate
-------	---------------------

Materials

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	velvety

Dimensions

Insertion depth	19 mm

Installation, mounting

Connection

Conductor cross-section (rigid)	max. 2 x 4 mm²
- with screw terminals	

Use

Differentiation characteristic 3 - Sales	with screw terminals

Standards

Standard	EMA 5-20 R
----------	------------

Safety

IK protection code against mecanical impacts	05
- without enhanced contact protection	

Identification

Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9



Inst	uc.	шо	ш

Information text Not UL-certified.