



6765836086



Socket outlet with earthing pin and hinged cover with enhanced touch protection, with screw-in lift terminals, Berker Q.1/Q.3/Q.7/Q.9, anthracite velvety, lacquered	
Technical features	
Architecture	
Fixing mode	flush-mounting
- 2pole + earth	
Connectivity	
Type of USB port	other
Main electrical features	
Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A
Cover, door	
Cover	Central cover plate
- with hinged cover that falls back	
Materials	
Colour of design line	anthracite
Colour	anthracite
Colour	anthracite charcoal grey
RAL colour	RAL 7021 - Black grey
Material / workmanship	lacquered
Material	thermoplastic
Surface appearance	velvety
Dimensions	
Insertion depth	31,3 mm
Installation, mounting	
Installation mode	with spreader claws
Connection	
Connection terminals	according to IEC 60884-1
- with screw-in lift terminals	
Use	
Differentiation characteristic 2 - Sales	with enhanced touch protection
Differentiation characteristic 3 - Sales	with screw-in lift terminals
Safety	
IK protection code against mecanical impacts	05
Enhanced contact protection	according to IEC 60884-1
- Enhanced contact protection	

Identification

Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9