product sheet 3315408982



3315408982

VGA socket outlet Berker S.1/B.3/B.7, white glossy

Technical features

| Connectivity |
|--------------|
|--------------|

| Connectivity | |
|--|---|
| - with straight outlet | |
| S-VGA compatible | |
| - with 15pole D-subminiature jack (fron | t) |
| Frequency | |
| Frequency range video | max. 160 MH: |
| Screen | |
| Resolution | max. 1280 x 1024 p |
| Materials | |
| Colour of design line | white |
| Colour | white |
| RAL colour | RAL 1013 - Oyster white |
| Material | Plastic/meta |
| Surface appearance | gloss |
| Dimensions | |
| Insertion depth | 12 mn |
| Installation, mounting | |
| Installation mode | without spreader claws, for screw fastening |
| Connection | |
| Connection | with 15pole D-subminiature double jac |
| with backside jack for connecting to p | re-assembled VGA cable |
| Equipment | |
| - with supporting ring | |
| Identification | |
| Application, usage | Communication technolog |
| Main design line | Berker S.1/B.3/B. |
| Secondary design line(s) | Berker S.1, Berker B.3, Berker B. |
| Instructions | |
| Information text | For connecting PCs, notebooks, etc. to display devices such as monitors (including LCD monitors and projectors., Observe the instructions of the cable and device manufacturers for maximum VG/ cable lengthsL Fränkischer "Multimedia tube" fo |

cable lengths!, Fränkische: "Multimedia tube" for laying pre-assembled connection cable, Art. no. 294.10.092, Installation recommendation: Kaiser: "Electronic box" for compliance with the permissible bending radii, Art. No. 1068-02 or 9062-74