



3315418989



## VGA socket outlet with screw-in lift terminals, Berker S.1/B.3/B.7, polar white glossy

Technical features

### Architecture

Technical version with screw-in lift terminals

## Connectivity

- with straight outlet
- S-VGA compatible
- with 15pole D-subminiature jack (front)

### Frequency

Frequency range video max. 160 MHz

### Screen

Resolution max. 1280 x 1024 px

### Materials

Colour of design linepolar whiteColourpolarwhiteRAL colourRAL 9010 - Pure whiteMaterialPlastic/metalSurface appearanceglossy

# Installation, mounting

Installation mode without spreader claws, for screw fastening

### Connection

Conductor cross-section max. 1,5 mm<sup>2</sup>

- with screw-in lift terminals for connection to 15-core VGA cable

# Equipment

- with supporting ring

### Use

Differentiation characteristic 3 - Sales with screw-in lift terminals

### Identification

Application, usage Communication technology
Main design line Berker S.1/B.3/B.7
Secondary design line(s) Berker S.1, Berker B.3, Berker B.7



### Instructions

Information text

For connecting PCs, notebooks, etc. to display devices such as monitors (including LCD monitors) and projectors., Observe the instructions of the cable and device manufacturers for maximum VGA cable lengths!, Fränkische: "Multimedia tube" for laying pre-assembled connection cable, Art. no. 294.10.092, Installation recommendation:

Kaiser: "Electronic box" for compliance with the permissible bending radii, Art. No. 1068-02 or