



41686084



Socket outlet with earthing contact USA/CANADA NEMA 5-20 R with screw terminals, Berker Q.1/Q.3/Q.7/Q.9

Technical features

Architecture

Fixing mode	flush-mounting
- 2pole + earth	

Main electrical features

Nominal voltage	125 V
Rated voltage	125 V AC
Frequency	50/60 Hz
Rated current	20 A

Cover, door

Cover	Central cover plate
-------	---------------------

Materials

Colour of design line	aluminium
Colour	aluminium
Colour	aluminium optics
RAL colour	RAL 9006 - White aluminium
Material / workmanship	lacquered
Material	thermoplastic
Surface appearance	velvety

Dimensions

Insertion depth	19 mm
-----------------	-------

Installation, mounting

Installation mode	without spreader claws, for screw fastening
-------------------	---

Connection

Conductor cross-section (rigid)	max. 2 x 4 mm ²
- with screw terminals	

Use

Differentiation characteristic 3 - Sales	with screw terminals
--	----------------------

Standards

Standard	NEMA 5-20 R
----------	-------------

Safety

IK protection code against mechanical impacts	02
- without enhanced contact protection	

Identification

Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9

Instructions

Information text	Not UL-certified.
------------------	-------------------